MRWF – 15mm GYPSUM BOARD

09 29 00/GC



Description

The Gypsemna's MOISTURE RESISTANCE FIREWALL (MRFW - 15mm) Type X Gypsum Board is an interior gypsum board consisting of a solid set, moisture and fire-resistive, Type X gypsum core enclosed in GREEN-colored face paper and a strong liner back paper. Gypsemna's MRFW Type X board features a specially formulated core providing moisture and fire resistance ratings when used in tested assemblies. Long edges are slightly tapered, allowing joints to be reinforced and concealed with joint tape and joint compound. The face paper and the back paper are 100 percent recycled.



Basic Uses

The Gypsemna's MOISTURE
RESISTANCE FIREWALL (MRFW 15mm) Type X Gypsum Board is
used for interior walls and ceilings in
all buildings categories applications
requiring moisture and fire ratings
an ideal choice as a moisture
resistant substrate for use in wet
areas such as kitchens and
bathrooms, behind sinks and basins
and in shower cubicles. Also
designed as a substrate for ceramic
tiles. It can be used for new
construction or renovations steel
framing.



Advantages

- Fire ratings up to four hours.
- Moisture Resistance.
- Consistently high quality.
- Uniformly flat, attractive appearance.
- High edge hardness.
- Uniform high-strength cores eliminate crumbling, cracking.
- Edge tapers consistent to form perfect joints.
- Excellent thermal barrier and sound attenuation qualities.
- Green certified.
- Qualifies as a low-VOC



Technical Data

Physical Properties

Thickness, Nominal 15mm
Width, Nominal 1200mm

Length, Standard 2400mm, 3000mm

Weight, Nominal 12.70kg/m2

Edges TE, SE

Color Green Color

Fire-Resistance Characteristics ASTM E84

Core Type Type X

Combustibility Non-combustible Core

Surface Burning Characteristics Class A

Flame Spread 0
Smoke Development 15

Standards and References

- ASTM C473 Standard Test Methods for

Physical Testing of Gypsum Panel Products

- ASTM C840 Standard Specification for

Application and Finishing of Gypsum Board

- ASTM E84 Standard Test Method for Surface

Burning Characteristics of Building Materials

- EN 520 Type I,F & H1 standard for Performance

of Gypsum Plasterboards

Get in touch

