

RG – 9.5mm GYPSUM BOARD

09 29 00/GC

Description

Gypsemna's REGULAR (RG - 9.5mm) Type C Gypsum Board is an interior gypsum board consisting of a solid set, Type C gypsum core enclosed in IVORY-colored face paper and a strong liner back paper. Gypsemna's RG Type C board. Long edges are slightly tapered, allowing joints to be reinforced and concealed with joint tape and joint compound. The face paper and the back paper are 100 percent recycled.

Basic Uses

The Gypsemna's REGULAR (RG - 9.5mm) Type C Gypsum Board is used for interior walls and ceilings in all buildings categories applications. It can be used for new construction or renovations steel framing. The boards are typically screwed to studs spaced maximum 600mm (24") also can be applied by laminating or with the use of an adhesive.

Advantages

- Consistently high quality.
- Uniformly flat, attractive appearance, no shadows
- High edge hardness.
- Uniform high-strength cores eliminate crumbling, cracking.
- Edge tapers consistent to form perfect joints.
- Excellent thermal barrier and sound attenuation qualities.
- Green certified.
- Qualifies as a low-VOC

Technical Data

Physical Properties

Thickness, Nominal	9.5mm
Width, Nominal	1200mm
Length, Standard	2400mm, 3000mm
Weight, Nominal	6.80kg/m ²
Edges	TE, SE
Color	Ivory Color

Fire-Resistance Characteristics ASTM E84

Core Type	Type C
Combustibility	Non-combustible Core
Surface Burning Characteristics	Class A
Flame Spread	0
Smoke Development	15

Standards and References

- ASTM C473 Standard Test Methods for Physical Testing of Gypsum Panel Products
- ASTM C840 Standard Specification for Application and Finishing of Gypsum Board
- ASTM E84 Standard Test Method for Surface Burning Characteristics of Building Materials
- EN 520 **Type A, Performance of Gypsum. Plasterboards**

Get in touch

info@gypsemna.com
www.gypsemna.com

technical@gypsemna.com
linkedin.com/company/gypsemna-company-llc/

